



# TRAVI "HE"

*ad ali larghe parallele - UNI 5397-64*

**A** = serie alleggerita    **B** = serie normale

**M** = serie rinforzata

	DIMENSIONI mm.				PESO kg./m.
	h	b	a	e	
<b>100 A</b>	96	100	5,0	8,0	16,7
<b>B</b>	100	100	6,0	10,0	20,4
<b>M</b>	120	106	12,0	20,0	41,8
<b>120 A</b>	114	120	5,0	8,0	19,9
<b>B</b>	120	120	6,5	11,0	26,7
<b>M</b>	140	126	12,5	21,0	52,1
<b>140 A</b>	133	140	5,5	8,5	24,7
<b>B</b>	140	140	7,0	12,0	33,7
<b>M</b>	160	146	13,0	22,0	63,2
<b>160 A</b>	152	160	6,0	9,0	30,4
<b>B</b>	160	160	8,0	13,0	42,6
<b>M</b>	180	166	14,0	23,0	76,2
<b>180 A</b>	171	180	6,0	9,5	35,5
<b>B</b>	180	180	8,5	14,0	51,2
<b>M</b>	200	186	14,5	24,0	88,9
<b>200 A</b>	190	200	6,5	10,0	42,3
<b>B</b>	200	200	9,0	15,0	61,3
<b>M</b>	220	206	15,0	25,0	103,0
<b>220 A</b>	210	220	7,0	11,0	50,5
<b>B</b>	220	220	9,5	16,0	71,5
<b>M</b>	240	226	15,5	26,0	117,0
<b>240 A</b>	230	240	7,5	12,0	60,3
<b>B</b>	240	240	10,0	17,0	83,2
<b>M</b>	270	248	18,0	32,0	157,0
<b>260 A</b>	250	260	7,5	12,5	68,2
<b>B</b>	260	260	10,0	17,5	93,0
<b>M</b>	290	268	18,0	32,5	172,0

	DIMENSIONI mm.				PESO kg./m.
	h	b	a	e	
<b>280 A</b>	270	280	8,0	13,0	76,4
<b>B</b>	280	280	10,5	18,0	103,0
<b>M</b>	310	288	18,5	33,0	189,0
<b>300 A</b>	290	300	8,5	14,0	88,3
<b>B</b>	300	300	11,0	19,0	117,0
<b>M</b>	340	310	21,0	39,0	238,0
<b>320 A</b>	310	300	9,0	15,5	97,6
<b>B</b>	320	300	11,5	20,5	127,0
<b>M</b>	359	309	21,0	40,0	245,0
<b>340 A</b>	330	300	9,5	16,5	105,0
<b>B</b>	340	300	12,0	21,5	134,0
<b>M</b>	377	309	21,0	40,0	248,0
<b>360 A</b>	350	300	10,0	17,5	112,0
<b>B</b>	360	300	12,5	22,5	142,0
<b>M</b>	395	308	21,0	40,0	250,0
<b>400 A</b>	390	300	11,0	19,0	125,0
<b>B</b>	400	300	13,5	24,0	155,0
<b>M</b>	432	307	21,0	40,0	256,0
<b>450 A</b>	440	300	11,5	21,0	140,0
<b>B</b>	450	300	14,0	26,0	171,0
<b>M</b>	478	307	21,0	40,0	263,0
<b>500 A</b>	490	300	12,0	23,0	155,0
<b>B</b>	500	300	14,5	28,0	187,0
<b>M</b>	524	306	21,0	40,0	270,0
<b>600 A</b>	590	300	13,0	25,0	178,0
<b>B</b>	600	300	15,5	30,0	212,0
<b>M</b>	620	305	21,0	40,0	285,0